RESOLUTION NO. 48-82

BUDGET TRANSFER - ELECTION DEPARTMENT

WHEREAS, a request has been received from the Mason County Election Department for a transfer of funds; and

WHEREAS, there are funds available within the Election Department Budget to accommodate said transfer; and

WHEREAS, the request appears to be reasonable and necessary;

NOW, THEREFORE, BE IT HEREBY RESOLVED by the Board of Mason County Commissioners that the following amounts be transferred:

\$1,332.00 from the Holding Fund (301-00)

to: Capital Outlay Line Item 109 (514-32-60)

BE IT FURTHER RESOLVED that the Mason County Auditor be authorized to make the necessary transfer entries on the ledger cards affecting the Election Department Budget.

ADOPTED this 6th day of July, 1982.

BOARD OF COUNTY COMMISSIONERS MASON COUNTY, WASHINGTON

Chairman

Commi

Commissioner

ATTEST:

Toele

Clerk of the Board

cc: Auditor Cmmrs Treasurer Election Dept Accounting Dept (2)

14.08.190 Section 301(b) Amended - Permits

a) Section 301(b)(1) is to read as follows:

 One-story detached accessory buildings used as tool sheds, playhouses and similar uses. [,-provided-the-projected roof-area-does-not-exceed-120-square-feet.]

b) The following subsections are added to Section 301(b):

13. Re-roofing of single Family residences, except when re-roofing structures with two or more existing layers of roof covering.

14. Detached (free standing) carports and garages constituting group M-1 occupancies.

15. Agricultural buildings as defined in Section 402, PROVIDED that in no event should fruit or vegetables or crops of the tree or vine stored in such buildings constitute combustible stock for the purposes of the Uniform Fire Code and PROVIDED further that such buildings be set back 50 feet from any adjacent residential structures and 50 feet from any property line.

16. Demolition of any private structure, except when explosives are used in such demolition.

14.08.200 Section 3203(d)(3)(H) Amended - Shake Felt

a) Section $320\frac{3}{4}(d)(3)(H)$ is to read as follows:

H. Wood shakes. Shakes may be applied to roofs with solid or spaced sheathing. In wind-driven-snow areas sheathing shall be solid and the shakes shall be applied over an underlayment of not less than Type 15 felt.

Shakes shall be laid with a side lap of not less than 11/2 inches between joints in adjacent courses. Spacing between shakes shall be not less than 3/8 inch nor more than 5/8 inch.

Shakes shall be fastened to the sheathing with two nails only, positioned approximately 1 inch from each edge and approximately 2 inches above the exposure line. The starter course at the eaves shall be doubled. The bottom or first layer may be either shakes or shingles.